

# Roxar Pig detector

Non-intrusive acoustic sensor

Data Sheet



## Real time pig detection for water, oil, gas or multiphase pipelines

Roxar Pig detectors are non-intrusive devices that utilize the acoustic noise generated by travelling pigs to identify pig passed signals in any water, oil, gas or multiphase pipeline flows. The units are compact, designed for easy installation, minimal maintenance and do not require a PC or laptop for daily use\* .

The system provides the operator with the accurate time at which a pig passes a given point and indicates the amount of pipeline debris pushed ahead by a cleaning pig.

All types of pig can be detected using the Roxar Pig detector without any requirement for pig inserts or the typical installation requirements of intrusive systems (tapping, welding etc.).

\*PC/Laptop required for setup & configuration purposes only unless software option 2 is supplied.



INTERPRETATION



MODELING



SIMULATION



WELL & COMPLETION



PRODUCTION & PROCESS

## Specifications

### General Specifications

#### Model:

- Roxar Pig detector

#### Suitable Pig Types:

- All pig types can be detected

### Detector Specifications

#### Detector Housing Material:

- 316 Stainless Steel

#### Dimensions / Weight:

- 88 mm (OD) x 100 mm / 3.0 Kg

#### Installation:

- Fixed onto outside of pipe (non-intrusive)

#### Ingress Protection:

- IP 67

#### Hazardous Area Classification / Location:

- EEx ia / Zone 0, 1 or 2

#### Hazardous Area Certification:

- CSA: Class I Division 1 Groups C, D T6/T5
- ATEX: Ex II 1 G EEx ia IIB T6/T5

#### Pipe Surface Temperature:

- -40°C to 115°C
- Higher range available on request

#### Ambient Temperature Range:

- -40°C to 80°C

#### Communication:

- Serial SW protocol overlain on power cable

#### Field Cable Type (Roxar optional supply or by 'others'):

- Screened twisted pair (0.75 mm<sup>2</sup>)
- Common pair for power and signal

#### Maximum Field Cable Length:

- Up to 1500 m depending on L/R ratio

### Calculation & Interface Unit (CIU)

#### Power Consumption:

- 2 W (including sensor and safety barrier)

#### Supply Voltage:

- 24 V DC

#### Modbus RTU Input / Output:

- 1 off process bus: 2 wire RS485
- 1 off service bus: 2 wire RS485 or 3 wire RS232
- Up to 32 units on the same bus with RS485

#### Analogue Output:

- 1 off 4-20 mA passive output for pig passed / raw data

#### Voltage-free Contact:

- Configurable to represent pig passed / technical alarm
- Local light indicator reset box available as an option

#### Data Storage:

- Up to 90 days based on 10 s averaging interval

#### Installation:

- DIN-rail mountable

#### Dimensions / Weight:

- 23 mm + 6 mm x 99 mm x 113 mm (WxLxH) / 0.2 Kg

#### Location:

- Safe area or optional field enclosure

### Safety Barrier

#### Type / Hazardous Area Classification:

- MTL 7787+ / EEx ia IIC
- Others available on request

#### Installation:

- DIN-rail mountable

#### Dimensions / Weight:

- 12.6 mm x 105 mm x 90 mm (WxLxH) / 0.14 Kg

#### Location:

- Safe area or optional field enclosure

### Power Supply (Optional)

#### Input Voltage:

- 100-240 V AC, 50/60 Hz

#### Output Voltage:

- 24 V DC

#### Installation:

- DIN-rail mountable

#### Location:

- Safe area or optional field enclosure

### Software

#### Option 1:

- CIU service software

#### Option 2:

- Server and client software

## Roxar Pig detector



[www.roxar.com](http://www.roxar.com)

For further information please contact your regional office or email: [info@roxar.com](mailto:info@roxar.com) or visit [www.roxar.com](http://www.roxar.com).

Scandinavia  
CIS  
Europe/Africa  
America

Tel: +47 51 81 88 00  
Tel: +7 495 504 3405  
Tel: +44 1224 411 200  
Tel: +1 713 334 2222

Middle East  
Asia Pacific  
Australia

Tel: +973 17 517 111  
Tel: +603 2162 4450  
Tel: +61 8 9315 9500



INTERPRETATION



MODELING



SIMULATION



WELL & COMPLETION



PRODUCTION & PROCESS